

# CHANGE AGENT

Compound Magic / Pure Alchemy

|                         |   |
|-------------------------|---|
| Construction            | Tufted, Textured Loop Pile  |
| Face Fibre              | ECONYL® 100% recycled Nylon 6   |
| Soil Release            | StainSmart® for soil release, liquid repellence   |
| Finished Face Weight    | 490 g/m <sup>2</sup>  |
| Gauge                   | 47.2 / 10 cm  |
| Rows                    | 44 / 10 cm  |
| Tuft Density            | 207,874/m <sup>2</sup>  |
| Finished Pile Height    | 2.5 mm  |
| Standard Backing        | WellBAC™ Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack® on request |
| Nominal Total Thickness | 8.3 mm  |
| Plank Size              | 25 cm x 100 cm  |
| Nominal Total Weight    | 3800 g/m <sup>2</sup>   |
| Planks Per Box          | 12 (3m <sup>2</sup> )   |

## PERFORMANCE

|  |   |
|--|---|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl-s1  |
| Flammability (Radiant Panel ASTM-E-648)          | Class 1   |
| Flammability (Hot Metal Nut BS4790)              | Low Radius of Char  |
| Use Classification (EN 1307)                     | Class 33 Heavy Commercial Use   |
| Castor Chair (BS EN 985:2001)                    | Class A - Intensive use (r value ≥ 2.4)                                   |
| Static Electricity (ISO 6356)                    | Pass ≤ 2.0 KV Permanent Conductive Fibre                                  |
| Impact Sound (ISO 10140-3)                       | 31 dB   |
| Sound Absorption (ISO354)                        | 0.25 Class E  |
| Alpha s values                                   | 125Hz 0.05, 250Hz 0.05, 500Hz 0.40, 1000Hz 0.20, 2000Hz 0.25, 4000Hz 0.35 |

## ENVIRONMENTAL

69% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,  
4.36 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon (EPD calculation A1-A3)  
Cradle to Gate footprint 100% off set

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS

[www.millikenfloors.com/gb/tech](http://www.millikenfloors.com/gb/tech)

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

|               |             |
|---------------|-------------|
|               |             |
| Ashlar Random | Herringbone |

## CE / UKCA

|                                      |                                      |  |  |  |  |
|--------------------------------------|--------------------------------------|--|--|--|--|
|                                      |                                      |  |  |  |  |
| DOP-2895-1004-02<br>BS EN 14041:2018 | DOP-0338-1004-02<br>BS EN 14041:2018 |  |  |  |  |