

LIGHTBOX



| | |
|-------------------------|---------------------------------------------------------------------------------------------------------------|
| Construction | Tufted, Textured Loop Pile |
| Face Fibre | ECONYL® 100% recycled Nylon 6 |
| Soil Release | StainSmart® for soil release, liquid repellence |
| Finished Face Weight | 490 g/m ² |
| Gauge | 47.2 / 10 cm |
| Rows | 44 / 10 cm |
| Tuft Density | 207,874/m ² |
| Finished Pile Height | 2.5 mm |
| Standard Backing | WellBAC™ Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack® on request |
| Nominal Total Thickness | 8.3 mm |
| Plank Size | 25 cm x 100 cm |
| Nominal Total Weight | 3800 g/m ² |
| Planks Per Box | 12 (3m ²) |

PERFORMANCE

| | |
|--------------------------------------------------|---------------------------------------------------------------------------|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl-s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Castor Chair (BS EN 985:2001) | Class A - Intensive use (r value ≥ 2.4) |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 31 dB |
| Sound Absorption (ISO354) | 0.25 Class E |
| Alpha s values | 125Hz 0.05, 250Hz 0.05, 500Hz 0.40, 1000Hz 0.20, 2000Hz 0.25, 4000Hz 0.35 |

ENVIRONMENTAL

69% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,
4.36 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

www.millikenfloors.com/gb/tech

| | | | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

INSTALLATION

| | |
|---------------|-------------|
| | |
| Ashlar Random | Herringbone |

CE / UKCA

| | | | | | |
|--------------------------------------|--------------------------------------|--|--|--|--|
| | | | | | |
| DOP-2895-1004-02 BS EN 14041:2018 | DOP-0338-1004-02 BS EN 14041:2018 | | | | |